## **Lithium-ion Battery Module**



Items	iStoragE B5L-S1	iStoragE B5-S1	iStoragE B5-S2
General			
Cell technology	LiFePO4		
Energy capacity	5kWh		
Usable capacity	5kWh		
Scalability	8		
Scalable capacity range	5~40kWh		
Rated power	2.5kW	4kW	4kW
Voltage range	360~500Vdc		650~900Vdc
Maximum charge current	6.94A	11.11A	6.15A
Maximum discharge current	6.94A 8.3A,10s	11.11A 13.33A,10s	6.15A 7.38A,10s
Dimension (W*H*D)	800*380*200mm/31.49*14.6*7.87in		
Weight	55kg/121.25lb		
Operating temperature	-20~50°C/-4~122°F		
Recommended operating temperature	15~30°C/59~86°F		
Storage temperature	-10~45°C/14~113°F		
Humidity	0~100%RH		
Altitude	2000m/6561ft		
Cooling type	Natural cooling		
Display	LED		
Communication interface	RS485, CAN		
Topology	Isolated		
Connection method	Floor or Wall mounted (optional)		
Certification	UL1973, UL60730, UN38.3, IEC 62619, IEC 60730, UN38.3		

 $<sup>^{\</sup>star}$  Specifications are subject to change without prior notice.