



PERC TECHNOLOGY MONOCRYSTALLINE PV MODULES EL-525~540M5-72H

144

CELLS



Micro-crack
Free



PID
Resistant



Salt Mist and Ammonia
Corrosion Resistant



German
Engineering



Tire 1 Bill
of Materials

GERMAN QUALITY

East Lux solar panel are constructed top grade materials, automated robotic lines, German technology and standards, making the quality difference.

PERFORMANCE& INVESTMENT GURANTEE

East Lux assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty.

Reliable Quality

- IEC61215, IEC61730(2016), IEC TS 62804-1-1:2020 (Anti PID)
- ISO 9001:2008: Quality management systems
- ISO 14001:2004: Environmental management systems
- BS OHSAS 18001: 2007: Occupational health and safety management system
- Positive power tolerance: 0~+5W
- 100% Triple EL inspection ensure free of defects.

PLUS SORTING


0~+5W postive sorting system to assure high output.

STABLE& STRONG

Capable to bear heavy snow loads up to 5400pa and wind loads up to 2400pa.

Linear Performance Warranty

12 years product warranty
25 years linear power warranty



German
Quality
Guarantee

Linear performance warranty
Standard performance warranty



SPECIFICATIONS

Module Type

	525M5-72H		530M5-72H		535M5-72H		540M5-72H	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Peak Power (Pmax)	525W	397W	530W	401W	535W	404W	540W	408W
Open Circuit Voltage (Voc)	49.15V	46.05V	49.30V	46.18V	49.45V	46.31V	49.60V	46.43V
Short circuit Current (Isc)	13.65A	10.97A	13.72A	11.01A	13.79A	11.05A	13.86A	11.09A
Peak Power Voltage (Vmpp)	41.15V	38.36V	41.31V	38.57V	41.47V	38.78V	41.64V	38.99V
Peak Power Current (Impp)	12.76A	10.35A	12.83A	10.39A	12.90A	10.43A	12.97A	10.37A
Component Efficiency (%)	20.3%		20.5%		20.6%		20.8%	


STC(Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25°C, AM1.5

NMOT(Nominal Module Operating Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Temperature Characteristics

Standard Working Temperature (NMOT)	45±2°C
Peak Power Temperature Coefficient	-0.350%/°C
Temperature Coefficient of Open Circuit Voltage	-0.276%/°C
Short-circuit Current Temperature Coefficient	+0.046%/°C
Working Temperature	-10°C to +85°C
Maximum System Voltage	DC 1500V (IEC)
Maximum Fuse Rating	25A
Power Tolerance	0~+5W

Module Dimensions(mm)



Specifications in this datasheet are subject to change without prior notice.


Mechanical Data

Cell Type	182*91mm Mono
Cell Orientation	144 6X24
Module Dimension	2279±2mm*1133±2mm*35±1mm
Weight	28.5kg±3%
Front	3.2mm high transmittance, reinforced glass
Aluminum Frame	Anodized Aluminum Alloy
Junction Box	4.0mm ³ , IP68 (3 Bypass Diodes)
Connecting Cable	Cable length, 300mm (+)/300mm (-)
Plug Connector	MC4 compatible connector
Maximum Mechanical Load	Front 5400Pa

I-V Curve

Current-Voltage Curve (540W)

Current (A)



STC

- Irradiance 1000W/m²
- Cell Temperature 25°C
- AM=1.5

NMOT

- Irradiance 800W/m²
- Ambient Temperature 20°C
- Wind Speed 1m/s
- AM=1.5

Packing Configuration

Modules per Pallet: 31pcs
Modules per 40' HQ Container: 620pcs
Modules per 20' GP Container: 150pcs