

All-in-one Liquid-cooled ESS Cabinet

ECO-E261LP-2A

Brief

The ECO-E261LP-2A features advanced pack-level liquid cooling and temperature balancing, maintaining cell temperature differences within 3 °C. This enhances cell temperature consistency and extends battery life. Its modular design enables flexible parallel configurations and higher energy density, significantly improving the cost-effectiveness, safety, and installation convenience of ESS projects.



Features

- Compact**
 1.4m² footprint only, easy transportation & fast installation.
- High Integration**
 261kWh energy in one cabinet with remarkable endurance.
- Efficient Cooling**
 Optimal in-PACK duct design, achieve high - efficient cooling and low energy consumption.
- Long Cycle Life**
 Over 8,000 times cycle life, excellent performance of battery system.

- Flexible Expansion**
 Modular design, simplified parallel expansion.
- Ultimate Safety**
 In-PACK fire warning and protection with aerosol, prevent heat diffusion and runaway.

Specifications

DC Side	
Cell Type	LFP / 314 Ah
Pack Configuration	52.2 kWh / 1P52S
System Configuration	261 kWh / 1P260S
Rated DC Voltage	832 V
DC Voltage Range	728 ~ 936 V
Max. Charge/Discharge Rate	0.5 P
Max. Depth of Discharge	100% (25 ± 2 °C)
AC Side	
Rated Output Power	125 kW
Rated AC Voltage	400 V
AC Voltage Range	±15%
Grid Type	3W+N+PE
Rated Frequency	50 Hz / 60 Hz
Power Factor	0.99/ -1 ~ +1
THDi	≤3%
DC Ratio	<0.5% Ipn
General	
Max. Round Trip Efficiency	89%
Cycle Life	≥ 8,000 cycles
Communication	Modbus TCP/IP
Fire Suppression System	Aerosol
Ingress Rating	IP55
Cooling	Liquid cooling+Forced air cooling
Operating Temperature	-25°C~55°C (Derating after 45°C)
Anticorrosion Rating	C4 (C5 optional)
Humidity	0~95% RH (non-condensing)
Noise	≤ 75 dB
Altitude	3000m (Derating above 2000m)
Dimensions (W*D*H)	1,050*1,350*2,400 mm
Weight	2,600 kg
Safety/EMC	UN38.3, IEC62619, IEC63056, IEC62477-1, IEC61000-6-2/4, UL9540A
Grid code	EN50549-1/-10, EN50549-2/-10, G99, VDE4105, NRS097, C10/11, CEI0-21, CEI0-16